

CHAPAS LAMINADO GRUESO

TABLA DE PESOS TEÓRICOS



Espesor		1,500	2,000	2,500
B.W.G.	mm.	X	X	X
		6,000	6,000	6,000
1/8"	3.20	226.08		
10	3.40	240.21		
	3.55	250.81		
	4.00	282.60		
3/16"	4.75	335.59		
	5.15	363.85		
1/4"	6.35	448.63	598.17	747.71
5/16"	8.00	565.20	753.60	942.00
3/8"	9.50	671.18	894.90	1,118.63
	12.50	883.13	1,177.50	1,471.88
1/2"	12.70	897.26	1,196.34	1,495.43
	15.00	1,059.75	1,413.00	1,766.25
5/8"	15.88	1,121.92	1,495.90	1,869.87
3/4"	19.05	1,345.88	1,794.51	2,243.14
7/8"	22.23	1,570.55	2,094.07	2,617.58
1"	25.40	1,794.51	2,392.68	2,990.85
1 1/4"	31.75	2,243.14	2,990.85	3,738.56
1 1/2"	38.10	2,691.77	3,589.02	4,486.28
1 3/4"	44.45	3,140.39	4,187.19	5,233.99
2"	50.80	3,589.02	4,785.36	5,981.70
2 1/4"	57.15	4,037.65	5,383.53	6,729.41
2 1/2"	63.50	4,486.28	5,981.70	7,477.13
3"	76.20	5,383.53	7,178.04	8,972.55
3 1/2"	88.90	6,280.79	8,374.38	10,467.98
4"	101.60	7,178.04	9,570.72	11,963.40
5"	127.00	8,972.55	11,963.40	14,954.25
6"	152.40	10,767.06	14,356.08	17,945.10

Calidad según Normas IRAM IAS 500 42 (F24/ F26 /F36), ASTM A36 (simil F26), SAE 1045 , Naval Gr A , ASTM A516 Gr 70, ASTM Gr 70 normalizada, EN 10025 S355 J2+N (eolico)

Peso Especifico utilizado:

7.85